

Section 2, T. 7. N. R. 1. E



20th day of March 1876 at One o'clock P.M. and continued from day to day until the survey was finished as follows commenced at the said East 1/4 m corner ran west (via S) to the west 1/4 mile corner distance 78.58 ch South side of section 79.50 ch West side 82.00 ch Established the following

corners referring to the above plat by the letters

- A. Set Stone for South 1/4 mile corner with: Buck 20 in S 10° W - 11 L Buck 12 in A 5° E
 B. Elm 4 feet dia S 52° E - 15 1/2 Ls Hickory 12 in A 52° W - 8 Links
 C. 100 Rods north of South 1/4 m corner with: Buck 8 in S 41° E - 13 1/2 Ls Buck 10 in S 21° W - 10 L
 D. on East Bank of Salt Creek with: water Buck 2 in S 8° W - 24 L - Stone with A 31° E - 10 L
 E. with: Buck 10 in A 85° E - 27 L - Buck 4 in A 32° W - 10 L Buck 18 in S 11° E - 2 L
 F. Stone corner with: Stone planted 10 Links East and another Stone 10 Ls north
 G. Centre corner with: Stone set for corner and: Stones planted for with: 10 Ls East & 10 Ls West
 H. Centre of A, B, & C Stone planted for corner & Stones buried 10 Ls west & 10 Ls East

Jesse Martin and James DeKard sworn as Chain bearers

W. H. Bailey
 11/26 Surveyor